# 2024 **VULCAN® 900 CUSTOM**





METALLIC MATTE DARK GRAY/METALLIC FLAT SPARK BLACK



## **POWER**

Engine	4-stroke, 55-degree V-twin, liquid-cooled
Displacement	903cc/55.10 cu in
Bore x Stroke	88.0 x 74.2mm
Compression Ratio	9.5:1
Maximum Torque	58.2 lb-ft @ 3,500 rpm
Fuel System	DFI® with 34mm throttle bodies (2), with sub-throttle valves
Ignition	TCBI with Electronic Advance
Transmission	5-speed with positive neutral finder
Final Drive	Kevlar-reinforced belt

#### **Front Tire** 80/90-21 **Rear Tire** 180/70-15 Single 300mm hydraulic disc **Front Brakes** Single 270mm hydraulic disc **Rear Brakes**

### **DETAILS**

@ 3,500 rpm	Frame Type	Semi-double cradle, high-tensile steel
	Rake/Trail	33°/7.2 in
1 34mm throttle bodies (2), with ttle valves	Overall Length	94.7 in
Electronic Advance	Overall Width	35.2 in
with positive neutral finder	Overall Height	44.1 in
inforced belt	Ground Clearance	5.5 in
	Seat Height	27.0 in
	Curb Weight	610.8 lb*
owa telescopic fork/5.9 in	Fuel Capacity	5.3 gal
	Wheelbase	64.8 in
<sup>®</sup> swingarm, 7-way adjustable eload/4.1 in	Color Choices	Metallic Matte Dark Gray/Metallic Flat Spark Black
	Warranty	12 Month Limited Warranty

### Front Suspension /

PERFORMANCE

41mm Sho

Wheel Travel

Rear Suspension / Wheel Travel Uni-Trak® spring pre

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2024 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit uruguay.kawasaki-la.com for full product details.