## MULE™ 4010 TRANS4x4®









Drum

## **POWER**

Engine 4-stroke, 2-cylinder, OHV, 90° V-twin, Liquid-cooled

Displacement 617cc

Maximum Torque 34.7 lb-ft @ 2,500 rpm

Bore x Stroke 2.99 x 2.68 in

Compression Ratio 10:3:1

Fuel System DFI® with 34mm Mikuni throttle body

Transmission Continuously Variable Transmission (CVT) with

(H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear

differential with differential lock

Engine Braking No

Alternator Output 23 amp

(max)

Ground Clearance 7.1 in
Fuel Capacity 6.3 gal
Turning Radius 12.8 ft

Cargo Bed 50.4 x 47.6 x 11.2 in (2-person) / 30.3 x 47.6 x 11.2 in (4person)

(LxWxH)

**Rear Brakes** 

Cargo Bed Load 800 lb (2-person) / 401 lb (4-person)

Capacity

**DETAILS** 

**Overall Height** 

Payload Capacity 1,330 lb

Seating Capacity 2-4

Towing Capacity 1,200 lb

Lighting (2) Halogen headlights (2) tail/brake lights

## **CAPABILITY**

Front Suspension / MacPherson Strut/3.9 in Wheel Travel

Rear Suspension / Wheel Travel

DeDion Axle/2.8 in

Front Tires 23x11.00-10

Rear Tires 23x11.00-10

Steering Rack-and-pinion w/ Electric Power Steering (EPS)

Park Brake Type Independent, Mechanical Drum

Front Brakes Drum

Overall Length 128.5 in

Overall Width 58.5 in

Curb Weight 1,587.6 lb\*

Wheelbase 85.2 in

Instruments Parking brake warning light, coolant temperature warning light, 12V DC outlet, fuel gauge, hour meter

Color Choices Dark Royal Red, Timberline Green

75.8 in

Warranty Kawasaki STRONG 3-Year Limited Warranty

Scan with camera to view videos, key features and more

