


2022

# KLX<sup>®</sup>300SM

**Kawasaki**  
Let the Good Times Roll<sup>®</sup>



## POWER

Engine	4-stroke single, DOHC, liquid-cooled
Displacement	292cc
Bore x Stroke	78.0 x 61.2mm
Compression Ratio	11.1:1
Fuel System	DFI <sup>®</sup> with 34mm Keihin throttle body
Ignition	CDI
Transmission	6-speed, return shift with wet multi-disc manual clutch
Final Drive	Chain

## PERFORMANCE

Front Suspension / Wheel Travel	43mm inverted cartridge fork with adjustable compression damping / 9.1 in
Rear Suspension / Wheel Travel	Uni-Trak <sup>®</sup> gas charged shock with piggyback reservoir with adjustable rebound damping and spring preload/ 8.1 in
Front Tire	110/70-17

Rear Tire	130/70-17
Front Brakes	Single 300mm petal disc with a dual-piston caliper
Rear Brakes	Single 240mm petal disc with single-piston caliper

## DETAILS

Frame Type	Semi Double Cradle
Rake/Trail	25.0° / 2.8 in
Overall Length	86.4 in
Overall Width	31.1 in
Overall Height	45.1 in
Ground Clearance	9.3 in
Seat Height	33.9 in
Curb Weight	304.3 lb*
Fuel Capacity	2.0 gal
Wheelbase	56.5 in
Color Choices	Lime Green/Ebony, Ebony
Warranty	12 Months

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit [uruguay.kawasaki-la.com](http://uruguay.kawasaki-la.com) for full product details.