MULE SX™ 4x4 XC LE FI







I)	N	V	N	F	R
		u	м.			•

Engine 4-stroke, single-cylinder, OHV, air-cooled

Displacement 401cc

Maximum Torque 21.4 lb-ft @ 2400 rpm

Bore x Stroke 3.23x2.99 in

Compression Ratio 8.6:1

Fuel System Fuel injection

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking N

Alternator Output 22.9 amp

(max)

erential lock

22.7 amp

CAPABILITY

Front Suspension / Wheel Travel MacPherson Strut/3.1 in

Rear Suspension / Wheel Travel

Unit Swingarm/3.1 in

Front Tires 26x9.00-12

Rear Tires 26x9.00-12

Steering Rack-and-pinion

Park Brake Type Independent, Mechanical Drum

Front Brakes Drum
Rear Brakes Drum

Additional Features

Warranty

Color Choices

Ground Clearance 8.1 in

Fuel Capacity 4.2 gal

Turning Radius 11.8 ft

Cargo Bed

Dimensions (LxWxH)

Cargo Bed Load

Capacity

Payload Capacity 884 lb

Seating Capacity 2

Towing Capacity 1100 lb*

Lighting (4) LED headlights, tail/brake lights

35.6 x 40.9 x 9.6 in

DETAILS

Overall Length 106.7 in

Overall Width 52.6 in

Overall Height 75.0 in

Curb Weight 1098.1 lb**

Wheelbase 70.1 in

Instruments Fuel gauge, hour meter, oil temp light, parking brake

ugnt

tures Roof, Under Seat Storage, LED Headlights, Painted Body

Panels

Metallic Onyx Black

Kawasaki 3-Year Limited Warranty

Scan with camera to view videos, key features and more.

