

2023

KX™ 250X

Kawasaki
Let the Good Times Roll®



POWER

Engine	4-stroke single, DOHC, liquid-cooled
Displacement	249cc
Bore x Stroke	78.0 x 52.2mm
Compression Ratio	14.1:1
Fuel System	DFI® with 44mm Keihin throttle body and dual injectors
Ignition	Digital CDI
Transmission	5-speed, return shift, with wet multi-disc manual clutch
Final Drive	Chain

Rear Tire	110/100-18
Front Brakes	Single semi-floating 270mm Braking® petal disc with dual-piston caliper
Rear Brakes	Single 240mm Braking® petal disc with single-piston caliper

DETAILS

Frame Type	Aluminum perimeter
Rake/Trail	27.8/4.8 in
Overall Length	85.4 in
Overall Width	32.3 in
Overall Height	49.6 in
Ground Clearance	13.0 in
Seat Height	37.2 in
Curb Weight	230.1 lb without fuel/240.2 lb*
Fuel Capacity	1.64 gal
Wheelbase	58.3 in
Color Choices	Lime Green
Warranty	Not Available

PERFORMANCE

Front Suspension / Wheel Travel	48mm inverted telescopic coil spring fork with 23-way compression damping and 20-way rebound damping /12.4 in
Rear Suspension / Wheel Travel	Uni-Trak® with dual-range (2.25 turns high speed/21-way low-speed) compression damping, 38-way rebound damping and adjustable preload/12.4 in
Front Tire	80/100-21

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit uruguay.kawasaki-la.com for full product details.