

2023

KX™ 450X

Kawasaki
Let the Good Times Roll®



POWER

Engine	4-stroke single, DOHC, liquid-cooled
Displacement	449cc
Bore x Stroke	96.0 x 62.1mm
Compression Ratio	12.5:1
Fuel System	DFI® with 44mm Keihin throttle body
Ignition	Digital CDI with 3 Coupler Options
Transmission	5-speed, return shift, with wet multi-disc manual clutch and hydraulic clutch actuation
Final Drive	Chain

Front Tire	80/100-21
Rear Tire	120/90-18
Front Brakes	Single semi-floating 270mm Braking® petal disc with dual-piston caliper
Rear Brakes	Single 240mm Braking® petal disc with single-piston caliper

PERFORMANCE

Front Suspension / Wheel Travel	49mm inverted telescopic coil-spring fork with 16-way compression damping and 16-way rebound damping/12.0 in
Rear Suspension / Wheel Travel	Uni-Trak® gas charged shock with piggyback reservoir with dual-range (4 turns stepless high speed/19-way low-speed) compression damping, 22-way rebound damping and adjustable preload/12.1 in

DETAILS

Frame Type	Aluminum perimeter
Rake/Trail	27.6° / 4.7 in
Overall Length	86.0 in
Overall Width	32.3 in
Overall Height	49.8 in
Ground Clearance	13.2 in
Seat Height	37.4 in
Curb Weight	235.8 lb without fuel / 246.0 lb*
Fuel Capacity	1.64 gal
Wheelbase	58.5 in
Color Choices	Lime Green
Warranty	Not Available

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit uruguay.kawasaki-la.com for full product details.