## MULE SX™ 4x4 XC FI









## **POWER**

Engine 4-stroke, single-cylinder, OHV, air-cooled

Displacement 401cc

Maximum Torque 21.4 lb-ft @ 2,400 rpm

Bore x Stroke 3.23x2.99 in

Compression Ratio 8.6

Fuel System Fuel injection

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

22.9 amp

Engine Braking N

**Alternator Output** 

(max)

Rear Brakes Drum

Ground Clearance 8.1 in

Fuel Capacity 4.2 gal

Turning Radius 11.8 ft

Cargo Bed Dimensions (LxWxH)

Cargo Bed Load

Capacity
Payload Capacity

900 lb

399 lb

Seating Capacity 2

**Towing Capacity** 

1,100 lb\*\*

. .

**Lighting** (2) Halogen headlights, tail/brake lights

35.6 x 40.9 x 9.6 in

## **CAPABILITY**

Front Suspension / MacPherson Strut/3.1 in Wheel Travel

Rear Suspension /

Unit Swingarm/3.1 in

Wheel Travel
Front Tires

26x9.00-12

**Rear Tires** 26x9.00-12

Steering Rack-and-pinion

**Park Brake Type** 

Independent, Mechanical Drum

Front Brakes Drum

## **DETAILS**

**Overall Width** 

**Curb Weight** 

Warrantv

Overall Length 106.7 in

Overall Height 73.4 in

Wheelbase 70.1 in

**Instruments** Fuel gauge, hour meter, oil temp light, parking brake

ight

52.6 in

1,082.7 lb\*

Color Choices Timberline Green, Firecracker Red

Kawasaki STRONG 3-Year Limited Warranty

Scan with camera to view videos, key features and more.

