## NINJA® ZX™-10R KRT EDITION







P	N	V	V	F	R
	u			_	•

4-stroke, In-Line Four, DOHC, 16-valve, liquid-**Engine** 

cooled

13.0:1

Displacement 998cc

**Bore x Stroke** 76.0 x 55.0mm

Compression

**Ratio** 

DFI® w/47mm Mikuni throttle bodies (4) with oval **Fuel System** 

sub-throttles, two injectors per cylinder

Ignition TCBI with digital advance and Sport-Kawasaki

TRaction Control (S-KTRC)

6-speed, return shift **Transmission** 

**Final Drive** Sealed chain

**Electronic Rider** 

Aids

Electronic Cruise Control, Kawasaki Launch Control Mode (KLCM), Kawasaki Sport TRaction Control (S-KTRC), Kawasaki Engine Braking Control, Kawasaki Quick Shifter (KQS) (upshift & downshift), Kawasaki Corner Management

Function (KCMF)

## **PERFORMANCE**

**Front Suspension** / Wheel Travel

43mm inverted Balance Free Fork, adjustable stepless rebound and compression damping, spring preload adjustability/4.7 in

**Rear Suspension** / Wheel Travel

Horizontal back-link with Balance Free gascharged shock, stepless, dual-range (low-/highspeed) compression damping, stepless rebound damping, fully adjustable spring preload/4.5 in

**Front Tire** 120/70 ZR17

**Rear Tire** 190/55 ZR17

**Front Brakes** Brembo® dual semi-floating 330mm discs with

dual radial mounted monobloc 4-piston calipers, (and Kawasaki Intelligent Braking System - KIBS)

Single 220mm disc with aluminium single-piston **Rear Brakes** 

caliper, (and Kawasaki Intelligent Braking System

- KIBS)

## **DETAILS**

Aluminum perimeter **Frame Type** 

Rake/Trail NON ABS: 25.0° / 4.1 in / ABS: 25.0° / 4.2 in

**Overall Length** 82.1 in

**Overall Width** 29.5 in

**Overall Height** 46.7 in

**Ground Clearance** 5.3 in

**Seat Height** 32.9 in

**Curb Weight** NON ABS: 452.0 lb / ABS: 456.4 lb\*

**Fuel Capacity** 4.5 gal

Wheelbase 57.1 in

**Special Features** 4.3" Full-Color TFT Instrumentation, Smartphone

Connectivity via RIDEOLOGY THE APP

**Color Choices** LIME GREEN / EBONY

12 Month Limited Warranty Warranty

Scan with camera to view videos. key features and more.

