NINJA® ZX™-10R KRT EDITION







D	N	V	V	E	D
Г	u	N.	٧	E	П

4-stroke, In-Line Four, DOHC, 16-valve, liquid-**Engine**

cooled

13.0:1

Displacement 998cc

Bore x Stroke 76.0 x 55.0mm

Compression

Fuel System

Ratio

DFI® w/47mm Mikuni throttle bodies (4) with oval

sub-throttles, two injectors per cylinder

TCBI with digital advance and Sport-Kawasaki Ignition

TRaction Control (S-KTRC)

6-speed, return shift **Transmission**

Sealed chain **Final Drive**

Electronic Rider

Aids

Electronic Cruise Control, Kawasaki Launch Control Mode (KLCM), Kawasaki Sport TRaction Control (S-KTRC), Kawasaki Engine Braking Control, Kawasaki

Quick Shifter (KQS) (upshift & downshift), Kawasaki

Corner Management Function (KCMF)

PERFORMANCE

Front Suspension / Wheel Travel

43mm inverted Balance Free Fork, adjustable stepless rebound and compression damping, spring preload adjustability/4.7 in

Rear Suspension / Wheel Travel

Horizontal back-link with Balance Free gas-charged shock, stepless, dual-range (low-/high-speed) compression damping, stepless rebound damping,

fully adjustable spring preload/4.5 in

Front Tire 120/70 ZR17

Rear Tire 190/55 ZR17

Brembo® dual semi-floating 330mm discs with dual **Front Brakes**

> radial mounted monobloc 4-piston calipers, (and Kawasaki Intelligent Braking System - KIBS)

Single 220mm disc with aluminium single-piston **Rear Brakes**

caliper, (and Kawasaki Intelligent Braking System -

KIBS)

DETAILS

Overall Height

Frame Type Aluminum perimeter

NON ABS: 25.0° /4.1 in / ABS: 25.0° /4.2 in Rake/Trail

Overall Length 82.1 in

Overall Width 29.5 in

Ground Clearance 5.3 in

Seat Height 32.9 in

Curb Weight NON ABS: 452.0 lb / ABS: 456.4 lb*

46.7 in

Fuel Capacity 4.5 gal

Wheelbase 57.1 in

Color Choices LIME GREEN / EBONY

12 Month Limited Warranty Warranty

Scan with camera to view videos. key features and more.

