## NINJA® ZX™-10RR







D	N	١	A	Ι		D
	u	l	т	1	CI	М

Engine 4-stroke, In-Line Four, DOHC, 16-valve, liquid-cooled

Displacement 998cc

Bore x Stroke 76.0 x 55.0mm

Compression Ratio 13.0

Fuel System DFI® w/47mm Mikuni throttle bodies (4) with oval

sub-throttles, two injectors per cylinder

Ignition TCBI with digital advance and Sport-Kawasaki

TRaction Control (S-KTRC)

Transmission 6-speed, return shift

Final Drive Sealed chain

Electronic Rider

Electronic Rider Aids Electronic Cruise Control, Kawasaki Launch Control Mode (KLCM), Kawasaki Intelligent anti-lock Brake System (KIBS), Kawasaki Sport TRaction Control (S-KTRC), Kawasaki Engine Braking Control, Kawasaki Quick Shifter (KQS) (upshift & downshift), Kawasaki Corner Management Function (KCMF)

## **PERFORMANCE**

Front Suspension / Wheel Travel

43mm inverted Balance Free Fork, adjustable stepless rebound and compression damping, spring preload adjustability/4.7 in

Rear Suspension / Wheel Travel

Horizontal back-link with Balance Free gas-charged shock, stepless, dual-range (low-/high-speed) compression damping, stepless rebound damping, fully adjustable spring preload/4.5 in

Front Tire 120/70 ZR17

**Rear Tire** 190/55 ZR17

Front Brakes Intelligent Braking (KIBS), Brembo® dual semi-floating

330mm discs with dual radial mounted monobloc 4-

piston calipers

Rear Brakes KIBS-supported, single 220mm disc with aluminum

single-piston caliper

## **DETAILS**

Frame Type Aluminum perimeter

Rake/Trail 25.0°/4.2 in

Overall Length 82.1 in

Overall Width 29.5 in

Overall Height 46.7 in

**Ground Clearance** 5.3 in

Seat Height 32.9 in

Curb Weight 456.4 lb\*

Fuel Capacity 4.5 gal

Wheelbase 57.1 in

Special Features 4.3" Full-Color TFT Instrumentation, Smartphone

Connectivity via RIDEOLOGY THE APP

Color Choices Lime Green

**Warranty** 12 Month Limited Warranty

Scan with camera to view videos, key features and more.

