# 2024 **VULCAN® 900 CUSTOM**





METALLIC MATTE DARK GRAY/METALLIC FLAT SPARK BLACK



## **POWER**

Engine	4-stroke, 55-degree V-twin, liquid-cooled
Displacement	903cc/55.10 cu in
Bore x Stroke	88.0 x 74.2mm
Compression Ratio	9.5:1
Maximum Torque	58.2 lb-ft @ 3,500 rpm
Fuel System	DFI® with 34mm throttle bodies (2), with sub-throttle valves
Ignition	TCBI with Electronic Advance
Transmission	5-speed with positive neutral finder
Final Drive	Kevlar-reinforced belt

#### **Front Tire** 80/90-21 **Rear Tire** 180/70-15 Single 300mm hydraulic disc **Front Brakes** Single 270mm hydraulic disc **Rear Brakes**

### **DETAILS**

Туре S	Semi-double cradle, high-tensile steel
Trail 3	33° /7.2 in
ll Length	94.7 in
ll Width 3	35.2 in
ll Height 4	44.1 in
-	5.5 in
eight 2	27.0 in
Veight 6	610.8 lb*
apacity 5	5.3 gal
base 6	64.8 in
	Metallic Matte Dark Gray/Metallic Flat Spark Black
nty 1	12 Month Limited Warranty
	Trail Il Length Il Width Il Height d nce leight Veight apacity base Choices

#### Front Suspension / Wheel Travel

PERFORMANCE

41mm Show

Rear Suspension / Wheel Travel

Uni-Trak® spring prel

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit uruguay.kawasaki-la.com for full product details.