Z900RS ABS







D	N	N	M	Г	D
Г	u	ľ	٧	E	π

Engine 4-stroke, 4-cylinder, DOHC, 16-valve, liquid-

cooled

Displacement 948cc

Bore x Stroke 73.4 x 56.0mm

Compression

Ratio

10.8:1

Maximum Torque 72.3 lb-ft @ 6,500 rpm

Fuel System DFI® with Keihin 36mm throttle bodies

Ignition TCBI with Electronic Advance

Transmission 6-speed, return shift

Final Drive Sealed chain

Electronic Rider

Aids

Economical Riding Indicator, Kawasaki TRaction Control (KTRC - 3 Modes), Anti-lock Brake System

PERFORMANCE

Front Suspension / Wheel Travel

Inverted telescopic fork with (13-way) adjustable compression and rebound (11-way) damping, spring preload (15-turn)/4.7

Rear Suspension / Wheel Travel

Horizontal back-link swingarm with stepless adjustable rebound damping and spring preload/5.5 in

Front Tire 120/70 ZR17

Rear Tire 180/55 ZR17

Front Brakes Dual 300mm discs with four-piston calipers, ABS

Rear Brakes Single 250mm disc with single-piston caliper,

DETAILS

Trellis, high tensile steel **Frame Type**

Rake/Trail 25.0°/3.9 in

82.7 in **Overall Length**

Overall Width 34.1 in

Overall Height 45.3 in

5.1 in Ground Clearance

Seat Height 32.9 in

Curb Weight 471.9 lb* 50-State Model

Fuel Capacity 4.5 gal

Wheelbase 57.9 in

Color Choices Metallic Diablo Black

Warranty 12 Month Limited Warranty



