KLX®140R L









90/100-16

piston caliper

piston caliper

POWER

Engine 4-stroke single, SOHC, air-cooled

Displacement 144cc

Bore x Stroke 58.0 x 54.4mm

Compression

Ratio

9.5:1

Fuel System 20mm Keihin carburetor

Ignition Digital DC-CDI

Transmission 5-speed, return shift, with wet multi-disc

manual clutch

Final Drive Chain

DETAILS

Rear Tire

Front Brakes

Rear Brakes

Frame Type High-tensile steel, box-section perimeter

Single 220mm petal disc with a dual-

Single 186mm petal disc with single-

Rake/Trail 27°/3.8 in

Overall Length 74.6 in

Overall Width 31.1 in

Overall Height 42.3 in

Ground

Clearance

Seat Height

Curb Weight 209.4 lb*

Fuel Capacity 1.5 gal

Wheelbase 50.6 in

Color Choices Lime Green, Battle Gray

10.0 in

31.5 in

Warranty 6 Month Limited Warranty

PERFORMANCE

Front Suspension / Wheel Travel 33mm telescopic fork/7.1 in

Rear Suspension / Wheel Travel Uni-Trak® linkage system and single shock with piggyback reservoir, fully adjustable preload and 22-way rebound damping/7.1

ın

Front Tire 70/100-19



