





METALLIC MATTE DARK GRAY/METALLIC SPARK BLACK



	1	П	١.		
r	U	ľ	Ν	r	K

**Engine** 4-stroke, 2-cylinder, DOHC, liquid-cooled

**Displacement** 649cc

**Bore x Stroke** 83.0 x 60.0mm

Compression

Ratio

Maximum

**Torque** 

**Fuel System** 

DFI® with Keihin 36mm throttle bodies

10.8:1

Ignition

6-speed, return shift

TCBI with Electronic Advance

48.5 lb-ft @ 6,500 rpm

**Transmission** 

Sealed chain

**Final Drive** 

**Electronic Rider** 

Aids

Economical Riding Indicator, Kawasaki TRaction Control (KTRC - 3 Modes), Anti-lock

**Brake System (ABS)** 

160/60 ZR17

**Front Brakes** 

Dual 300mm petal-style discs with two-piston

calipers, (and ABS)

**Rear Brakes** 

**Rear Tire** 

Single 220mm petal-style disc, (and ABS)

## **DETAILS**

**Frame Type** Trellis, high tensile steel

24.0°/3.9 in Rake/Trail

**Overall Length** 80.9 in

**Overall Width** 30.1 in

41.9 in **Overall Height** 

Ground Clearance

**Seat Height** 

**Curb Weight** 414.5 lb\* (ABS) / 412.3 lb\* (non-ABS) 50-State

Model

5.1 in

31.1 in

**Fuel Capacity** 4.0 gal

Wheelbase 55.5 in

**Special Features** Smartphone Connectivity via RIDEOLOGY THE

APP, TFT Instrumentation

**Color Choices** 

Candy Persimmon Red/Ebony, Metallic Matte Dark Gray/Metallic Spark Black

12 Month Limited Warranty Warranty

## **PERFORMANCE**

Front Suspension / **Wheel Travel**  Telescopic fork/4.9 in

**Rear Suspension** / Wheel Travel

Horizontal back-link with adjustable preload,

swingarm/5.1 in

**Front Tire** 120/70 ZR17

Scan with camera to view videos. key features and more.

