

2025

KLX[®]110R



- LIME GREEN
- BATTLE GRAY



POWER

| | |
|-------------------|---|
| Engine | 4-stroke, single-cylinder, SOHC, air-cooled |
| Displacement | 112cc |
| Bore x Stroke | 53.0 x 50.6mm |
| Compression Ratio | 9.5:1 |
| Fuel System | Keihin PB18 carburetor and screw type throttle limiter on grip housing |
| Ignition | DC-CDI |
| Transmission | 4-speed, return shift, automatic centrifugal and wet, multi-disc clutch |
| Final Drive | Chain |

PERFORMANCE

| | |
|---------------------------------|---|
| Front Suspension / Wheel Travel | 30mm hydraulic telescopic fork/4.3 in |
| Rear Suspension / Wheel Travel | Swingarm with single hydraulic shock/4.3 in |

| | |
|--------------|--------------------------------------|
| Front Tire | 2.50 x 14 |
| Rear Tire | 3.00 x 12 |
| Front Brakes | 90mm mechanical drum, cable actuated |
| Rear Brakes | 110mm mechanical drum, rod actuated |

DETAILS

| | |
|------------------|------------------------------------|
| Frame Type | Backbone frame, high-tensile steel |
| Rake/Trail | 24.8° /2.0 in |
| Overall Length | 61.4 in |
| Overall Width | 25.6 in |
| Overall Height | 37.6 in |
| Ground Clearance | 8.5 in |
| Seat Height | 26.8 in |
| Curb Weight | 167.5 lb* |
| Fuel Capacity | 1.0 gal |
| Wheelbase | 42.3 in |
| Color Choices | Lime Green, Battle Gray |
| Warranty | 6 Month Limited Warranty |

Scan with camera
to view videos,
key features
and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit uruguay.kawasaki-la.com for full product details.