



2025

# KLX<sup>®</sup>110R L



-  LIME GREEN
-  BATTLE GRAY



## POWER

Engine	4-stroke, single-cylinder, SOHC, air-cooled
Displacement	112cc
Bore x Stroke	53.0 x 50.6mm
Compression Ratio	9.5:1
Fuel System	Keihin PB18 carburetor and screw type throttle limiter on grip housing
Ignition	DC-CDI
Transmission	4-speed, return shift, wet multi-disc manual clutch
Final Drive	Chain

## PERFORMANCE

Front Suspension / Wheel Travel	30mm hydraulic telescopic fork/5.5 in
Rear Suspension / Wheel Travel	Swingarm with single hydraulic shock/5.2 in

Front Tire	2.50 x 14
Rear Tire	3.00 x 12
Front Brakes	90mm mechanical drum, cable actuated
Rear Brakes	110mm mechanical drum, rod actuated

## DETAILS

Frame Type	Backbone frame, high-tensile steel
Rake/Trail	24.2° / 1.9 in
Overall Length	61.4 in
Overall Width	25.6 in
Overall Height	39.0 in
Ground Clearance	10.4 in
Seat Height	28.7 in
Curb Weight	167.5 lb*
Fuel Capacity	1.0 gal
Wheelbase	42.3 in
Color Choices	Lime Green, Battle Gray
Warranty	6 Month Limited Warranty

Scan with camera  
to view videos,  
key features  
and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit [uruguay.kawasaki-la.com](http://uruguay.kawasaki-la.com) for full product details.