


2025

KLX[®]140R F

Kawasaki
Let the Good Times Roll[®]



POWER

| | |
|--------------------------|--|
| Engine | 4-stroke, single-cylinder, SOHC, air-cooled |
| Displacement | 144cc |
| Bore x Stroke | 58.0 x 54.4mm |
| Compression Ratio | 9.5:1 |
| Fuel System | Keihin PB20 carburetor |
| Ignition | Digital DC-CDI |
| Transmission | 5-speed, return shift, with wet multi-disc manual clutch |
| Final Drive | Chain |

| | |
|---------------------|--|
| Rear Tire | 4.10 x 18 |
| Front Brakes | Single 220mm petal disc with a dual-piston caliper |
| Rear Brakes | Single 186mm petal disc with single-piston caliper |

PERFORMANCE

| | |
|--|--|
| Front Suspension / Wheel Travel | 33mm telescopic fork/7.5 in |
| Rear Suspension / Wheel Travel | Uni-Trak [®] linkage system and single shock with piggyback reservoir, 20-way rebound damping and threaded preload adjustability/7.9 in |
| Front Tire | 2.75 x 21 |

DETAILS

| | |
|-------------------------|---|
| Frame Type | High-tensile steel, box-section perimeter |
| Rake/Trail | 27.0° / 4.6 in |
| Overall Length | 78.9 in |
| Overall Width | 31.1 in |
| Overall Height | 44.7 in |
| Ground Clearance | 12.4 in |
| Seat Height | 33.9 in |
| Curb Weight | 218.2 lb* |
| Fuel Capacity | 1.5 gal |
| Wheelbase | 52.4 in |
| Color Choices | Lime Green, Battle Gray |
| Warranty | 6 Month Limited Warranty |

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit uruguay.kawasaki-la.com for full product details.