

2025

# KLX<sup>®</sup>140R L

**Kawasaki**  
Let the Good Times Roll<sup>®</sup>



## POWER

<b>Engine</b>	4-stroke, single-cylinder, SOHC, air-cooled
<b>Displacement</b>	144cc
<b>Bore x Stroke</b>	58.0 x 54.4mm
<b>Compression Ratio</b>	9.5:1
<b>Fuel System</b>	Keihin PB20 carburetor
<b>Ignition</b>	Digital DC-CDI
<b>Transmission</b>	5-speed, return shift, with wet multi-disc manual clutch
<b>Final Drive</b>	Chain

<b>Rear Tire</b>	90/100-16
<b>Front Brakes</b>	Single 220mm petal disc with a dual-piston caliper
<b>Rear Brakes</b>	Single 186mm petal disc with single-piston caliper

## PERFORMANCE

<b>Front Suspension / Wheel Travel</b>	33mm telescopic fork/7.1 in
<b>Rear Suspension / Wheel Travel</b>	Uni-Trak <sup>®</sup> linkage system and single shock with piggyback reservoir, fully adjustable preload and 22-way rebound damping/7.1 in
<b>Front Tire</b>	70/100-19

## DETAILS

<b>Frame Type</b>	High-tensile steel, box-section perimeter
<b>Rake/Trail</b>	27.0°/3.8 in
<b>Overall Length</b>	74.6 in
<b>Overall Width</b>	31.1 in
<b>Overall Height</b>	42.3 in
<b>Ground Clearance</b>	10.0 in
<b>Seat Height</b>	31.5 in
<b>Curb Weight</b>	209.4 lb*
<b>Fuel Capacity</b>	1.5 gal
<b>Wheelbase</b>	50.6 in
<b>Color Choices</b>	Lime Green, Battle Gray
<b>Warranty</b>	6 Month Limited Warranty

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit [uruguay.kawasaki-la.com](http://uruguay.kawasaki-la.com) for full product details.