## KLX®230R









## **POWER**

**Engine** 4-stroke, single-cylinder, SOHC, air-cooled **Displacement** 233cc **Bore x Stroke** 67.0 x 66.0mm Compression 9.4:1 **Ratio** DFI® with 32mm Keihin throttle body **Fuel System** TCBI with electronic advance Ignition **Transmission** 6-speed, return shift with wet multi-disc manual clutch

**Rear Tire** 100/100-18

Front Brakes Single 240mm petal disc with a dual-

piston caliper

**Rear Brakes** Single 220mm petal disc with single-

piston caliper

## **PERFORMANCE**

Chain

**Final Drive** 

Front
Suspension /
Wheel Travel

Rear
Suspension /
Wheel Travel

Uni-Trak® linkage system and single shock with adjustable spring preload/9.8 in

Front Tire

80/100-21

## **DETAILS**

High-tensile steel, box-section perimeter **Frame Type** Rake/Trail 25.4° / 4.2 in **Overall Length** 80.5 in **Overall Width** 33.3 in **Overall Height** 47.2 in Ground 11.4 in Clearance **Seat Height** 35.6 in **Curb Weight** 262.4 lb\* / 264.5 lb\* 50-State Model **Fuel Capacity** 1.7 gal

Wheelbase 54.1 in

**Color Choices** Lime Green, Battle Gray

**Warranty** 6 Month Limited Warranty

Scan with camera ( to view videos, key features and more.

