


2025

KLX[®] 230R S

Kawasaki
Let the Good Times Roll[®]



POWER

Engine	4-stroke, single-cylinder, SOHC, air-cooled
Displacement	233cc
Bore x Stroke	67.0 x 66.0mm
Compression Ratio	9.4:1
Fuel System	DFI [®] with 32mm Keihin throttle body
Ignition	TCBI with electronic advance
Transmission	6-speed, return shift with wet multi-disc manual clutch
Final Drive	Chain

Rear Tire	100/100-18
Front Brakes	Single 240mm petal disc with a dual-piston caliper
Rear Brakes	Single 220mm petal disc with single-piston caliper

PERFORMANCE

Front Suspension / Wheel Travel	37mm telescopic fork/8.7 in
Rear Suspension / Wheel Travel	Uni-Trak [®] linkage system and single shock with adjustable spring preload/8.8 in
Front Tire	80/100-21

DETAILS

Frame Type	High-tensile steel, box-section perimeter
Rake/Trail	24.6°/3.9 in
Overall Length	80.5 in
Overall Width	33.3 in
Overall Height	46.7 in
Ground Clearance	10.6 in
Seat Height	34.4 in
Curb Weight	262.4 lb* / 264.5 lb* 50-State Model
Fuel Capacity	1.7 gal
Wheelbase	53.3 in
Color Choices	Lime Green, Battle Gray
Warranty	6 Month Limited Warranty

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit uruguay.kawasaki-la.com for full product details.