MULE™ 4010 TRANS4x4®









POWER

Engine 4-stroke, 2-cylinder, OHV, 90° V-twin, Liquid-cooled

Displacement 617cc

Maximum Torque 34.7 lb-ft @ 2,500 rpm

Bore x Stroke 76.0 x 68.0mm

Compression Ratio 10:3:

Fuel System DFI® with 34mm Mikuni throttle body

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking N

Alternator Output

(max)

23 amp

Rear Brakes	Drum

Ground Clearance

Dimensions

Capacity

Fuel Capacity 6.3 gal

Turning Radius 12.8 ft

Cargo Bed 50.4 x 47.6 x 11.2 in (2-person) / 30.3 x 47.6 x 11.2 in (4-

(LxWxH)

Cargo Bed Load 800 lb (2-person) / 401 lb (4-person)

person)

7.1 in

Payload Capacity 1,330 lb

Seating Capacity 2-4

Towing Capacity 1,200 lb

Lighting (2) Halogen headlights, (2) tail/brake lights

CAPABILITY

Front Suspension / MacPherson Strut/3.9 in Wheel Travel

Rear Suspension / Wheel Travel DeDion Axle/2.8 in

23 x 11-10

Front Tires 23 x 11-10

Steering Rack-and-pinion w/ Electric Power Steering (EPS)

Park Brake Type

Rear Tires

Independent, mechanical drum

Front Brakes Drum

DETAILS

Overall Length 128.5 in
Overall Width 58.5 in

Overall Height 75.8 in

Curb Weight 1,587.6 lb*

Wheelbase 85.2 in

Instruments Parking brake warning light, coolant temperature

warning light, 12V DC outlet, fuel gauge, hour meter

Color Choices Timberline Green, Dark Royal Red

Warranty Kawasaki STRONG 3-Year Limited Warranty

Scan with camera to view videos, key features and more.



