## **MULE PRO-DXT™ EPS**









## **POWER**

**Engine** 4-stroke, 3-cylinder, OHV, liquid-cooled, diesel

**Displacement** 993cc

**Maximum Torque** 38.3 lb-ft @ 2,400 rpm

**Bore x Stroke** 74.0 x 77.0mm

**Compression Ratio** 23.5:1

**Fuel System** Bosch in-line injection pump

**Transmission** Continuously Variable Transmission (CVT) with (H,L,N,R)

**Final Drive** Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

**Engine Braking** 

**Alternator Output** 55 amp

(max)

**Ground Clearance** 10.2 in

**Fuel Capacity** 7.9 gal

**Turning Radius** 16.0 ft

Cargo Bed 42.7 x 53.7 x 11.0 in (3-person) / 22.0 x 53.7 x 11.0 in (6-**Dimensions (LxWxH)** 

999 lb (3-person) / 350 lb (6-person)

person)

**Cargo Bed Load** Capacity

**Payload Capacity** 1,574 lb

**Seating Capacity** 3-person (1-row), 6-person (2-row)

**Towing Capacity** 2,000 lb

Lighting (2) Halogen headlights

## **CAPABILITY**

**Wheel Travel** 

Front Suspension / Double wishbone/8.7 in **Wheel Travel** 

**Rear Suspension /** Double wishbone/8.5 in (L)/8.7 in (R)

**Front Tires** 26 x 9-12 **Rear Tires** 26 x 11-12

**Steering** Electric Power Steering (EPS), Tilt steering

Independent, mechanical disc **Park Brake Type** 

**Front Brakes** Dual disc, 2-piston caliper

**Rear Brakes** Dual disc, 1-piston caliper

## **DETAILS**

**Overall Length** 133.3 in **Overall Width** 64.0 in

77.6 in **Overall Height** 

**Curb Weight** 1,942.6 lb\*

Wheelbase 92.3 in

Instruments Multi-function display includes digital speedometer, fuel

gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, glow plug indicator, CVT and EPS warning indicators, neutral, reverse and parking indicators, seatbelt reminder lamps

**Additional Features** Roof, Horn, Universal Key, High Visibility Orange

Seatbelts

**Color Choices** Super Black

Kawasaki STRONG 3-Year Limited Warranty Warranty

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.