MULE PRO-FXT™ 1000 LE RANCH EDITION









POWER

Engine 4-stroke, 2-cylinder, DOHC, liquid-cooled, gas

Displacement 999cc

Maximum Torque 61.5 lb-ft @ 4,500 rpm

Bore x Stroke 92.0 x 75.1mm

Compression Ratio

Fuel System DFI® with 38mm throttle body

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Selectable 2WD/4WD, shaft. Dual mode rear differential with **Final Drive**

differential lock

Engine Braking

Alternator Output 90 amp

(max)

Ground Clearance 12.6 in (max), 11.6 in (std)

Fuel Capacity 7.9 gal

Turning Radius 16.0 ft

Dimensions (LxWxH)

Cargo Bed Load Capacity

Payload Capacity

Seating Capacity

Towing Capacity

Lighting

3-person (1 row), 6 person (2 row)

1,616.3/1,263.5 lb CA Model

CAPABILITY

Front Suspension / Wheel Travel

Double wishbone/11.0 in

Rear Suspension / Wheel Travel

Double wishbone/10.1 in

Dual disc, 2-piston caliper

Front Tires 26 x 9-12, radial **Rear Tires** 26 x 11-12, radial

Steering Rack-and-pinion w/ Electric Power Steering (EPS), Tilt

Park Brake Type Independent, mechanical disc

Wheel Type Allov

Rear Brakes Dual disc, 1-piston caliper

(2) Halogen headlights, (2) LED headlights

42.7 x 53.7 x 11.0 in (3-person) / 22.0 x 53.7 x 11.0 in (6-person)

999 lb (3-person)/350 lb (6-person)/348 lb CA Model

DETAILS

135.8 in **Overall Length**

Overall Width 64.0 in

Overall Height 80.9 in

Estimated Dry Weight 1,891.9/1,894.1 lb** CA Model

1,966.9/1,969.1 lb* CA Model **Curb Weight**

Wheelbase 92.3 in

Instruments

Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters,

2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT and EPS warning indicators, neutral, reverse and parking

indicators, seatbelt reminder lamps

Additional Features Roof, Additional Front Cup Holders, WARN® VRX 45 Winch,

Premium Seats, Self-Leveling Rear Suspension

Color Choices Metallic Deep Red

Kawasaki STRONG 3-Year Limited Warranty Warrantv

Scan with camera to view videos, key features and more.

Front Brakes



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). **Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE™ side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2026 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit uruguay.kawasaki-la.com for full product details.