MULE PRO-FXT™ 1000 PLATINUM RANCH EDITION







POWER

Engine 4-stroke, 2-cylinder, DOHC, liquid-cooled, gas

Displacement 999cc

Maximum Torque 61.5 lb-ft @ 4,500 rpm

Bore x Stroke 92.0 x 75.1mm

Compression Ratio 10.1:1

Fuel System DFI® with 38mm throttle body

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential with

differential lock

Engine Braking Yes

Alternator Output 90 amp

(max)

Fuel Capacity 7.9 gal
Turning Radius 16.0 ft

Cargo Bed Dimensions (LxWxH)

wxn)

Cargo Bed Load Capacity

42.7 x 53.7 x 11.0 in (3-person) / 22.0 x 53.7 x 11.0 in (6-person)

999 lb (3-person)/350 lb (6-person)/348 lb CA Model

Payload Capacity
Seating Capacity

3-person (1 row), 6 person (2 row)

1,616.3/1,263.5 lb CA Model

Towing Capacity

2,000 lb

Lighting

(4) LED headlights

CAPABILITY

Front Suspension / Wheel Travel

Wheel Travel

Double wishbone/11.0 in

Rear Suspension / Wheel Travel Double wishbone/10.1 in

Front Tires
Rear Tires

26 x 9-12, radial 26 x 11-12, radial

Wheel Type

Allov

Steering

Rack-and-pinion w/ Electric Power Steering (EPS), Tilt steering

Park Brake Type

Independent, mechanical disc

Front Brakes
Rear Brakes

Dual disc, 2-piston caliper

Dual disc, 1-piston caliper

Ground Clearance

12.6 in (max), 11.6 in (std)

DETAILS

Overall Length 140.2 in

Overall Width 64.0 in

Overall Height

80.9 in

Estimated Dry Weight

1,955.8/1,958.0 lb** CA Model

Curb Weight

2.030.8/2.033.0 lb* CA Model

Wheelbase

92.3 in

Instruments

Mule: fund

Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters,

2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT and EPS warning indicators, neutral, reverse and parking

indicators, seatbelt reminder lamps

Additional Under Seat Storage Bin

Metallic Stardust White

Additional Features

Roof, Additional Front Cup Holders, WARN® VRX 45 Winch, Premium Seats, Premium Shoulder Pads, Self-Leveling Rear Suspension, Quad LED Headlights, Brush Guard, Headlight Guards, Rear Bumper, Anti-cinch Seat Belts, Rearview Mirror,

Color Choices

Warrantv

Kawasaki STRONG 3-Year Limited Warranty

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE™ side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit uruguay.kawasaki-la.com for full product details.