MULE SX™ 4x4 XC







POWER

Engine 4-stroke, single-cylinder, OHV, air-cooled

Displacement 401cc

Maximum Torque 21.4 lb-ft @ 2,400 rpm

Bore x Stroke 82.0 x 76.0mm

Compression Ratio 8.6:1

Fuel System Fuel Injection

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking N

Alternator Output 22.9 amp

(max)

Front Brakes Drum

Rear Brakes Drum

Ground Clearance 8.1 in

Fuel Capacity 4.2 gal

Turning Radius 11.8 ft

Cargo Bed 35.6 x 40.9 x 9.6 in Dimensions (LxWxH)

Cargo Bed Load

Capacity

399 lb

Payload Capacity 900 lb

Seating Capacity 2

Towing Capacity 1,100 lb**

Lighting (2) Halogen headlights, tail/brake lights

CAPABILITY

Front Suspension / Wheel Travel

MacPherson Strut/3.1 in

Rear Suspension / Wheel Travel

Rear Tires

Unit Swingarm/3.1 in

Front Tires 26 x 9-12

26 x 9-12

Steering Rack-and-pinion

Park Brake Type Independent, mechanical drum

DETAILS

Overall Length 106.7 in

Overall Width 52.6 in

Overall Height 73.4 in

Curb Weight 1,082.7 lb*

Wheelbase 70.1 in

Instruments Fuel gauge, hour meter, oil temp light, parking brake

light

Color Choices Metallic Sierra Blue

Warranty Kawasaki STRONG 3-Year Limited Warranty

Scan with camera to view videos, key features and more.

