NINJA H2® ABS









POWER

Horsepower **Maximum Torque**

Engine 4-stroke, in-line 4-cylinder, DOHC, 16-valve, liquid-cooled

Displacement 998cc

Bore x Stroke 76.0 x 55.0mm

Compression Ratio 8.5:1

Maximum 239.6 hp1 @ 11,500 rpm

Fuel System DFI® with 50mm throttle bodies (4) with dual injection;

Kawasaki Supercharger

104.9 lb-ft @ 11,000 rpm

Ignition TCBI with Digital Advance

Transmission 6-speed, return shift, dog-ring

Final Drive Sealed chain

Electronic Rider Aids Economical Riding Indicator, Kawasaki Cornering Management Function (KCMF), Kawasaki TRaction Control

(KTRC), Kawasaki Launch Control Mode (KLCM), IMU-Enhanced Chassis Orientation Awareness, Kawasaki Intelligent anti-lock Brake System (KIBS), Kawasaki Engine Brake Control (KEBC), Kawasaki Quick Shifter (KQS) (upshift

& downshift), Öhlins Electronic Steering Damper

PERFORMANCE

Front Suspension / **Wheel Travel**

43mm inverted Kayaba AOS-II fork with adjustable rebound and compression damping, spring preload adjustability and top-out springs/4.7 in

Rear Suspension / **Wheel Travel**

Uni-Trak®, Öhlins TTX36 gas-charged shock with piggyback reservoir, 24-way compression and rebound damping adjustability, 15-way spring preload adjustability, and top-

outspring/5.3 in

Front Tire 120/70-17

Rear Tire 200/55-17

Front Brakes Dual 330mm semi-floating discs with dual radial-mount,

opposed 4-piston Brembo Stylema® calipers, Kawasaki

Intelligent anti-lock Brake System (KIBS)

Rear Brakes Single 250mm disc with opposed 2-piston caliper, Kawasaki Intelligent anti-lock Brake System (KIBS)

DETAILS

Frame Type Trellis, high-tensile steel, with swingarm mounting plate

24.5° / 4.1 in Rake/Trail

Overall Length 82.1 in

Overall Width 30.3 in

Overall Height 44.3 in

Ground Clearance 5.1 in

Seat Height 32.5 in

480.7 lb** **Estimated Dry** Weight

Curb Weight 524.8 lb*

Fuel Capacity 4.5 gal

Wheelbase 57.3 in

Special Features Supercharged engine, All-digital TFT color

> Instrumentation, All-LED lighting, Highly Durable Paint, Smartphone Connectivity via RIDEOLOGY THE APP

Color Choices Mirror Coated Spark Black

12 Month Limited Warranty Warranty

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). ¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard. KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit uruguay.kawasaki-la.com for full product details.