

2025

NINJA[®] ZX[™]-10R

Kawasaki
Let the Good Times Roll[®]



METALLIC FLAT SPARK BLACK/EBONY



POWER

Engine	4-stroke, In-Line Four, DOHC, 16-valve, liquid-cooled
Displacement	998cc
Bore x Stroke	76.0 x 55.0mm
Compression Ratio	13.0:1
Maximum Horsepower	196.0 hp ¹ @ 11,500 rpm
Fuel System	DFI [®] with 47mm throttle bodies
Ignition	TCBI with Digital Advance
Transmission	6-speed, return shift
Final Drive	Sealed chain
Electronic Rider Aids	Öhlins Electronic Steering Damper, Electronic Cruise Control, Power Modes, Kawasaki Launch Control Mode (KLCM), Kawasaki Intelligent anti-lock Brake System (KIBS) (ABS only), Sport-Kawasaki TRaction Control (S-KTRC), Kawasaki Engine Braking Control, Kawasaki Quick Shifter (KQS) (upshift & downshift), Kawasaki Corner Management Function (KCMF)

Front Tire	120/70 ZR17
Rear Tire	190/55 ZR17
Front Brakes	Brembo dual semi-floating 330mm discs with dual radial mounted monobloc 4-piston calipers, Kawasaki Intelligent anti-lock Brake System (KIBS) (ABS only)
Rear Brakes	Single 220mm disc with aluminum single-piston caliper, Kawasaki Intelligent anti-lock Brake System (KIBS) (ABS only)

DETAILS

Frame Type	Aluminum perimeter
Rake/Trail	25.0° / 4.1 in
Overall Length	82.1 in
Overall Width	29.5 in
Overall Height	46.7 in
Ground Clearance	5.3 in
Seat Height	32.9 in
Curb Weight	456.4 lb* (ABS), 452.0 lb* (non-ABS)
Fuel Capacity	4.5 gal
Wheelbase	57.1 in
Special Features	4.3" Full-Color TFT Instrumentation, Smartphone Connectivity via RIDEOLGY THE APP
Color Choices	Metallic Flat Spark Black/Ebony
Warranty	12 Month Limited Warranty

PERFORMANCE

Front Suspension / Wheel Travel	43mm inverted Balance Free Fork, adjustable stepless rebound and compression damping, spring preload adjustability/4.7 in
Rear Suspension / Wheel Travel	Horizontal back-link with Balance Free gas-charged shock, adjustable compression damping, adjustable rebound damping, stepless adjustable spring preload/4.5 in

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.
 KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2024 Kawasaki Motors Corp., U.S.A.
 Specifications subject to change. Visit uruguay.kawasaki-la.com for full product details.