

2025

NINJA<sup>®</sup> ZX<sup>™</sup>-10R

Kawasaki

Let the Good Times Roll<sup>®</sup>





METALLIC FLAT SPARK BLACK/EBONY



POWER

|                       |  |
|-----------------------|--|
| Engine                | 4-stroke, In-Line Four, DOHC, 16-valve, liquid-cooled  |
| Displacement          | 998cc  |
| Bore x Stroke         | 76.0 x 55.0mm  |
| Compression Ratio     | 13.0:1   |
| Maximum Horsepower    | 196.0 hp <sup>1</sup> @ 11,500 rpm   |
| Fuel System           | DFI <sup>®</sup> with 47mm throttle bodies   |
| Ignition              | TCBI with Digital Advance  |
| Transmission          | 6-speed, return shift  |
| Final Drive           | Sealed chain   |
| Electronic Rider Aids | Öhlins Electronic Steering Damper, Electronic Cruise Control, Power Modes, Kawasaki Launch Control Mode (KLCM), Kawasaki Intelligent anti-lock Brake System (KIBS) (ABS only), Sport-Kawasaki TRaction Control (S-KTRC), Kawasaki Engine Braking Control, Kawasaki Quick Shifter (KQS) (upshift & downshift), Kawasaki Corner Management Function (KCMF) |

PERFORMANCE

|                                 |   |
|---------------------------------|---|
| Front Suspension / Wheel Travel | 43mm inverted Balance Free Fork, adjustable stepless rebound and compression damping, spring preload adjustability/4.7 in                                       |
| Rear Suspension / Wheel Travel  | Horizontal back-link with Balance Free gas-charged shock, adjustable compression damping, adjustable rebound damping, stepless adjustable spring preload/4.5 in |

|              |  |
|--------------|--|
| Front Tire   | 120/70 ZR17  |
| Rear Tire    | 190/55 ZR17  |
| Front Brakes | Brembo dual semi-floating 330mm discs with dual radial mounted monobloc 4-piston calipers, Kawasaki Intelligent anti-lock Brake System (KIBS) (ABS only) |
| Rear Brakes  | Single 220mm disc with aluminum single-piston caliper, Kawasaki Intelligent anti-lock Brake System (KIBS) (ABS only)                                     |

DETAILS

|                  |   |
|------------------|---|
| Frame Type       | Aluminum perimeter  |
| Rake/Trail       | 25.0° /4.1 in   |
| Overall Length   | 82.1 in   |
| Overall Width    | 29.5 in   |
| Overall Height   | 46.7 in   |
| Ground Clearance | 5.3 in  |
| Seat Height      | 32.9 in   |
| Curb Weight      | 456.4 lb* (ABS), 452.0 lb* (non-ABS)  |
| Fuel Capacity    | 4.5 gal   |
| Wheelbase        | 57.1 in   |
| Special Features | 4.3" Full-Color TFT Instrumentation, Smartphone Connectivity via RIDELOGY THE APP |
| Color Choices    | Metallic Flat Spark Black/Ebony   |
| Warranty         | 12 Month Limited Warranty   |

Scan with camera  
to view videos,  
key features  
and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

<sup>1</sup>This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit [uruguay.kawasaki-la.com](http://uruguay.kawasaki-la.com) for full product details.