NINJA® ZX™-4R ABS









POWER

4-stroke, in-line 4-cylinder, DOHC, 16-valve, **Engine**

liquid-cooled

12.3:1

Displacement 399cc

Bore x Stroke 57.0 x 39.1mm

Compression

Ratio

Maximum

Horsepower

56.0 hp¹ @ 11,500 rpm

Maximum Torque 26.5 lb-ft @ 11,000 rpm

Fuel System DFI® with 34mm throttle valves (4)

Ignition TCBI with Digital Advance

Transmission 6-speed, return shift

Final Drive Chain

Electronic Rider

Aids

Economical Riding Indicator, Kawasaki TRaction Control (KTRC) (3-mode), Power Modes, Anti-lock Brake System (ABS)

PERFORMANCE

Front Suspension / Wheel Travel

37mm inverted Showa fork with SFF-BP

internals/4.7 in

Rear Suspension Horizontal back-link, Showa shock w/ adjustable / Wheel Travel

spring preload/4.4 in

Front Tire 110/70-17

Rear Tire 160/60-17

Front Brakes Dual 290mm semi-floating discs with radial-

mount 4-piston monobloc caliper and ABS

Single 220mm disc with single-piston caliper and **Rear Brakes**

ABS

DETAILS

Trellis, high-tensile steel **Frame Type**

Rake/Trail 23.5°/3.8 in

Overall Length 78.3 in

Overall Width 30.1 in

Overall Height 43.7 in

Ground Clearance 5.3 in

Seat Height 31.5 in

Curb Weight 414.5 lb*

Fuel Capacity 4.0 gal

Wheelbase 54.3 in

Special Features 4.3" Full-color TFT Instrumentation, Smartphone

Connectivity via RIDEOLOGY THE APP

Color Choices Metallic Spark Black

Warranty 12 Month Limited Warranty



