


2025

NINJA<sup>®</sup> ZX<sup>™</sup>-6R KRT EDITION

Kawasaki

Let the Good Times Roll<sup>®</sup>





LIME GREEN/EBONY/PEARL BLIZZARD WHITE

| POWER                           |  | Rear Tire        | 180/55 ZR17  |
|---------------------------------|--|------------------|--|
| Engine                          | 4-stroke, In-Line Four, DOHC, 16-valve, liquid-cooled  | Front Brakes     | Dual semi-floating 310mm discs with dual radial-mounted, monobloc, opposed 4-piston caliper, Kawasaki Intelligent anti-lock Brake System (KIBS) (ABS only) |
| Displacement                    | 636cc  | Rear Brakes      | Single 220mm petal discs with single-piston caliper, Kawasaki Intelligent anti-lock Brake System (KIBS) (ABS only)   |
| Bore x Stroke                   | 67.0 x 45.1mm  | DETAILS          |  |
| Compression Ratio               | 12.9:1   |                  |  |
| Maximum Horsepower              | 127.0 hp <sup>1</sup> @ 13,000 rpm   |                  |  |
| Fuel System                     | DFI <sup>®</sup> with 38mm Keihin throttle bodies (4) and oval sub-throttles   |                  |  |
| Ignition                        | TCBI with Electronic Advance   |                  |  |
| Transmission                    | 6-speed, return shift  | Frame Type       | Aluminum perimeter   |
| Final Drive                     | Sealed chain   | Rake/Trail       | 23.5° / 4.0 in   |
| Electronic Rider Aids           | Kawasaki Traction Control (KTRC), Power Modes (Full/Low), Kawasaki Intelligent anti-lock Brake System (KIBS) (ABS only), Kawasaki Quick Shifter (KQS) (upshift only)           | Overall Length   | 79.7 in  |
| PERFORMANCE                     |  | Overall Width    | 28.0 in  |
|                                 |  | Overall Height   | 43.3 in  |
|                                 |  | Ground Clearance | 5.1 in   |
|                                 |  | Seat Height      | 32.7 in  |
|                                 |  | Curb Weight      | 436.6 lb* (ABS), 432.2 lb* (non-ABS) 50-State Model, 434.4 lb* (ABS), 430.0 lb* (non-ABS) 49-State Model   |
| Front Suspension / Wheel Travel | 41mm inverted fork (SFF-BP) with rebound and compression damping and spring preload adjustability, and top-out springs/4.7 in  | Fuel Capacity    | 4.5 gal  |
| Rear Suspension / Wheel Travel  | Bottom-link Uni-Trak <sup>®</sup> with gas-charged shock, stepless compression damping adjustment, stepless adjustable rebound damping, fully adjustable spring preload/5.9 in | Wheelbase        | 55.1 in  |
| Front Tire                      | 120/70 ZR17  | Special Features | 4.3" Full-Color TFT Instrumentation, Smartphone Connectivity via RIDEOLGY THE APP  |
|                                 |  | Color Choices    | Lime Green/Ebony/Pearl Blizzard White  |
|                                 |  | Warranty         | 12 Month Limited Warranty  |



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

<sup>1</sup>This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit [uruguay.kawasaki-la.com](http://uruguay.kawasaki-la.com) for full product details.