## 2025 **RIDGE<sup>®</sup> XR**





METALLIC GRAYSTONE ICE GRAY

## **POWER**

Engine	4-stroke, DOHC, 4-valve In-Line Four-Cylinder, liquid-cooled
Displacement	999cc
Maximum Horsepower	116.0 hp <sup>1</sup> @ 8,500 rpm
Maximum Torque	73.8 lb-ft @ 8,000 rpm
Bore x Stroke	73.4 x 59.0mm
<b>Compression Ratio</b>	10.6:1
Fuel System	EFI
Ignition	TCBI with Digital Advance
Starting System	Electric
Transmission	Continuously Variable Transmission (CVT) with (H,L,N,R)
Final Drive	Selectable 4WD with locking front/rear differential, shaft
Engine Braking	Yes
Alternator Output (max)	85 amp
Electronic Rider Aids	Power Modes, Economical Riding Indicator

## **CAPABILITY**

Front Suspension / Wheel Travel	Long-Travel, Double Wishbone/12.7 in	Instruments	Digital speedometer, tachometer, fuel gauge, oc trip meters, total time, trip time, average speed, Driving Mode, Power Mode, clock, water temper
Rear Suspension / Wheel Travel	Long-Travel, Double Wishbone/12.7 in		voltage, oil change reminder, Bluetooth indicate Riding Indicator, maintenance reminder, high be
Front Tires	Duro 30 x 10-14		reverse, and warning lights (battery, EPS, CVT, se indicator, oil pressure, water temperature)
Rear Tires	Duro 30 x 10-14	Additional Features	Full Cab with HVAC, Adjustable driver/passenge
Wheel Type	14" Aluminum		FIT <sup>®</sup> , Full-color TFT Instrumentation with Smart Connectivity via RIDEOLOGY THE APP Powerspor
Steering	Rack-and-pinion w/ Electric Power Steering (EPS)		KQR™ system compatible
Front Brakes	Dual hydraulic 249mm discs with two-piston calipers	Color Choices	Metallic Graystone, Ice Gray
Rear Brakes	Dual hydraulic 249mm discs with single-piston calipers	Warranty	Kawasaki STRONG 3-Year Limited Warranty





\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). 1This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard. Specifications subject to change. Visit uruguay.kawasaki-la.com for full product details.

Fuel Capacity	12.9 gal
Turning Radius	15.0 ft
Cargo Bed Dimensions (LxWxH)	37.6 x 49.0 x 12.8 in
Cargo Bed Load Capacity	1,000/600 lb CA Model
Payload Capacity	1,499/1,100 lb CA Model
Seating Capacity	2, bucket seat
Towing Capacity	2,500 lb
Lighting	All-LED lighting

13.4/14.4 in (max preload); 13.4 in CA Model

## **DETAILS**

**Overall Length** 

**Overall Width** 

**Overall Height** 

Frame

Ground Clearance

overatt height	02.1111
Curb Weight	1,898.5/1,900.7 lb* CA Model
Wheelbase	90.7 in
Instruments	Digital speedometer, tachometer, fuel gauge, odometer, dual trip meters, total time, trip time, average speed, gear indicator, Driving Mode, Power Mode, clock, water temperature, battery voltage, oil change reminder, Bluetooth indicator, Economical Riding Indicator, maintenance reminder, high beam, neutral, reverse, and warning lights (battery, EPS, CVT, seatbelt, parking indicator, oil pressure, water temperature)
Additional Features	Full Cab with HVAC, Adjustable driver/passenger seats, ERGO- FIT®, Full-color TFT Instrumentation with Smartphone Connectivity via RIDEOLOGY THE APP Powersports, USB ports, KQR™ system compatible
Color Choices	Metallic Graystone, Ice Gray
Warranty	Kawasaki STRONG 3-Year Limited Warranty

Ladder type, tubular steel

125.4 in

64.0 in

82.1 in