## <sup>2025</sup> **Z650**

**POWER** 





METALLIC SPARK BLACK/GREEN

METALLIC MATTE DARK GRAY/METALLIC SPARK BLACK

Dual 300mm petal-style discs with two-piston



160/60-17

**Rear Tire** 

**Front Brakes** 

## Engine 4-stroke, 2-cylinder, DOHC, liquid-cooled Displacement 649cc Bore x Stroke 83.0 x 60.0mm Compression 10.8:1 Ratio 67.0 hp1 @ 8,000 rpm Maximum Horsepower **Maximum Torque** 48.5 lb-ft @ 6,700 rpm **Fuel System** DFI® with Keihin 36mm throttle bodies Ignition **TCBI with Electronic Advance** Transmission 6-speed, return shift **Final Drive** Sealed chain Economical Riding Indicator, Kawasaki TRaction **Electronic Rider** Control (KTRC - 3 Modes), Anti-lock Brake System Aids (ABS)

## PERFORMANCE

Front Suspension / Wheel Travel	41mm telescopic fork/4.9 in
Rear Suspension / Wheel Travel	Horizontal back-link with adjustable preload, swingarm/5.1 in
Front Tire	120/70-17

	calipers (and ABS)	
Rear Brakes	Single 220mm petal-style disc (and ABS)	
DETAILS		
Frame Type	Trellis, high tensile steel	
Rake/Trail	24.0°/3.9 in	
Overall Length	80.9 in	
Overall Width	30.1 in	
Overall Height	41.9 in	
Ground Clearance	5.1 in	
Seat Height	31.1 in	
Estimated Dry Weight	381.5 lb** (ABS) / 379.3 lb** (non-ABS) 50-State Model	
Curb Weight	414.5 lb* (ABS) / 412.3 lb* (non-ABS) 50-State Model	
Fuel Capacity	4.0 gal	
Wheelbase	55.5 in	
Special Features	4.3" All-digital TFT color Instrumentation, Smartphone Connectivity via RIDEOLOGY THE APP	
Color Choices	Metallic Matte Dark Gray/Metallic Spark Black, Metallic Spark Black/Green	
Warranty	12 Month Limited Warranty	

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). \*\*Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). \*This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard. KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE<sup>TM</sup> side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2024 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit uruguay.kawasaki-la.com for full product details.