

2026

TERYX® 4 H2

Kawasaki
Let the Good Times Roll®

- LIME GREEN
- ICE GRAY



POWER		Fuel Capacity	14.8 gal
Engine	4-stroke, DOHC, 4-valve, in-line 4-cylinder, liquid-cooled	Turning Radius	24.9 ft
Displacement	999cc	Cargo Bed Dimensions (LxWxH)	14.6 x 33.1 x 9.1 in
Maximum Horsepower	250.0 hp ¹ @ 9,000 rpm	Cargo Bed Load Capacity	300 lb
Maximum Torque	146.3 lb-ft @ 8,800 rpm	Payload Capacity	1,076 lb
Bore x Stroke	73.4 x 59.0mm	Seating Capacity	4-person (2 row), bucket seats with 4-point seatbelts
Compression Ratio	7.8:1	Lighting	All-LED lighting
Fuel System	DFI® with (4) 40mm throttle bodies with dual injection; Kawasaki Supercharger	DETAILS	
Ignition	TCBI with electronic advance	Frame	Ladder type, tubular steel
Starting System	Electric	Overall Length	159.4 in
Transmission	Continuously Variable Transmission (CVT) with (H,L,N,R)	Overall Width	74.0 in
Final Drive	Selectable 2WD/4WD with locking front differential, shaft	Overall Height	71.5 in
Engine Braking	Yes	Estimated Dry Weight	2,291.0 lb** / 2,293.2 lb** CA Model
Electronic Rider Aids	Economical Riding Indicator, Power Modes	Curb Weight	2,425.5 lb* / 2,427.7 lb* CA Model
CAPABILITY		Wheelbase	126.0 in
Front Suspension / Wheel Travel	Double wishbone, FOX 3.0 Internal Bypass shocks, adjustable compression damping and adjustable preload/23.2 in	Instruments	Digital speedometer, tachometer, fuel gauge, gear indicator (L, H, N, R), Driving Mode (2WD/4WD/4WD+Diff Lock), Power Mode (Full/Mid/Low), Economical Riding Indicator, connected indicator, clock, odometer, dual trip meters, total time, trip time, average speed, engine temperature, intake air temperature, battery voltage, boost pressure, CTV temperature, seatbelt warning lamp, maintenance reminder, oil warning lamp, engine check lamp, engine temperature warning lamp, neutral indicator, reverse indicator, headlight high-beam indicator, parking indicator lamp, battery warning lamp, EPS warning lamp, and CVT belt warning lamp
Rear Suspension / Wheel Travel	4-link trailing-arm rear suspension, FOX 3.0 Internal Bypass Shocks, adjustable compression damping and adjustable preload/24.0 in	Additional Features	7-in Full-color TFT Instrumentation with Smartphone Connectivity via RIDELOGY THE APP POWERSPORTS, Skid plates w/ drain holes, ERGO-FIT®, 2 DC outlets, 2 USB ports, 8 cup holders, Additional storage
Front Tires	Maxxis® Carnivore Plus 33 x 10.00R16	Color Choices	Lime Green, Ice Gray
Rear Tires	Maxxis® Carnivore Plus 33 x 10.00R16		
Wheel Type	16-in aluminum wheels		
Steering	Electric Power Steering (EPS) / rack-and-pinion		
Front Brakes	270mm dual hydraulic discs with 3-piston calipers		
Rear Brakes	270mm dual hydraulic discs with 2-piston calipers		
Ground Clearance	16.5 in (max) / 16.1 in (std)		

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.
KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: The Teryx® side x side can be hazardous to operate. For your safety: Always wear a helmet, eye protection and protective clothing. Never operate under the influence of drugs or alcohol. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Protect the environment. The Kawasaki Teryx side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. ©2026 Kawasaki Motors Corp., U.S.A.
Specifications subject to change. Visit uruguay.kawasaki-la.com for full product details.