

2026

VULCAN® S



-  METALLIC GRAPHITE GRAY/METALLIC SPARK BLACK
-  METALLIC FLAT SPARK BLACK



POWER		Rear Tire	
Engine	4-stroke, 2-cylinder, DOHC, liquid-cooled	Front Brakes	160/60-17
Displacement	649cc	Rear Brakes	Single 300mm disc with twin-piston caliper (and ABS)
Bore x Stroke	83.0 x 60.0mm		Single 250mm disc with single-piston caliper (and ABS)
Compression Ratio	10.8:1	DETAILS	
Maximum Horsepower	60 hp ¹ @ 7,500 rpm	Frame Type	High-tensile steel diamond frame
Maximum Torque	46.5 lb-ft @ 6,600 rpm	Rake/Trail	31° / 4.7 in
Fuel System	DFI® with 38mm throttle bodies (2), with sub-throttle valves	Overall Length	90.9 in
Ignition	TCBI with Electronic Advance	Overall Width	34.6 in
Transmission	6-speed with positive neutral finder	Overall Height	43.3 in
Final Drive	Sealed chain	Ground Clearance	5.1 in
Electronic Rider Aids	Economical Riding Indicator, Anti-lock Brake System (ABS)	Seat Height	27.8 in
PERFORMANCE		Estimated Dry Weight	467.5 lb** (ABS), 460.8 lb** (non-ABS)
Front Suspension / Wheel Travel	41mm telescopic fork/5.1 in	Curb Weight	498.3 lb* (ABS), 491.7 lb* (non-ABS)
Rear Suspension / Wheel Travel	Lay-down offset rear shock with linkage and adjustable preload/3.2 in	Fuel Capacity	3.7 gal
Front Tire	120/70-18	Wheelbase	62.0 in
		Special Features	ERGO-FIT®
		Color Choices	Metallic Graphite Gray/Metallic Spark Black, Metallic Flat Spark Black
		Warranty	12 Month Limited Warranty

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit uruguay.kawasaki-la.com for full product details.