

2024 Z500 SE ABS

Kawasaki
Let the Good Times Roll®



CANDY PERSIMMON RED/METALLIC FLAT SPARK BLACK/
METALLIC MATTE GRAPHENE STEEL GRAY



POTENCIA

| | |
|---------------------------------------|---|
| Motor | 4-stroke, Parallel Twin, DOHC, liquid-cooled |
| Cilindrada | 451cc |
| Diámetro por carrera | 70.0 x 58.6mm |
| Relación de compresión | 11.3:1 |
| Maximum Horsepower | 51.0 hp ¹ @ 10,000 rpm |
| Par motor máximo | 31.7 lb-ft @ 7,500 rpm |
| Sistema de combustible | DFI® with dual 32mm throttle bodies |
| Encendido | TCBI with Electronic Advance |
| Transmisión | 6-speed |
| Transmisión final | Sealed chain |
| Asistencia electrónica para el piloto | Economical Riding Indicator, Anti-lock Brake System (ABS) |

RENDIMIENTO

| | |
|--|--|
| Suspensión delantera/recorrido del neumático | 41mm hydraulic telescopic fork/4.7 in |
| Suspensión trasera/recorrido del neumático | Horizontal back-link with adjustable spring preload/5.1 in |
| Neumático delantero | 110/70-17 |
| Neumático trasero | 150/60-17 |

| | |
|-------------------|--|
| Frenos delanteros | Single 310mm semi-floating disc with 2-piston calipers and ABS |
| Frenos traseros | Single 220mm disc with single-piston caliper and ABS |

DETALLES

| | |
|----------------------------|---|
| Tipo de chasis | Trellis, high-tensile steel |
| Ángulo de dirección/Avance | 24.5° / 3.6 in |
| Largo total | 78.5 in |
| Ancho total | 31.5 in |
| Altura del asiento | 43.3 in |
| Distancia al suelo | 5.7 in |
| Altura del asiento | 30.9 in |
| Dry Weight | 339.6 lb** / 341.8 lb** 50-State Model |
| Peso en orden de marcha | 370.4 lb* / 372.6 lb* 50-State Model |
| Depósito de combustible | 3.7 gal |
| Distancia entre ejes | 54.1 in |
| Características especiales | ERGO-FIT®, Full-color TFT Instrumentation with Smartphone Connectivity via RIDEOLGY THE APP, USB-C outlet |
| Colores disponibles | Candy Persimmon Red/Metallic Flat Spark Black/Metallic Matte Graphenesteel Gray |
| Garantía | 12 Month Limited Warranty |

Escanear con cámara para ver videos, características clave y más.



*La tara incluye todos los materiales y fluidos necesarios para su correcto funcionamiento, el depósito lleno de combustible (con una capacidad superior al 90 %) y el kit de herramientas (si está incluido).

**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI SE PREOCUPA: Lea el Manual de usuario y todas las advertencias del producto. Lleve siempre puesto un casco protección para los ojos, y ropa adecuada. Nunca conduzca bajo la influencia de las drogas o el alcohol. Cumpla con el programa de mantenimiento en su manual del propietario. ©2024 Kawasaki Motors Corp., U.S.A.

Las especificaciones están sujetas a cambios. Visite uruguay.kawasaki-la.com para obtener detalles completos del producto.