

# 2025 Z650

**Kawasaki**  
Let the Good Times Roll®



METALLIC SPARK BLACK/GREEN



GRIS METALLIC MATTE DARK/NEGRO METALLIC SPARK



## POTENCIA

Motor	4-stroke, 2-cylinder, DOHC, liquid-cooled
Cilindrada	649cc
Diámetro por carrera	83.0 x 60.0mm
Relación de compresión	10.8:1
Maximum Horsepower	67.0 hp <sup>1</sup> @ 8,000 rpm
Par motor máximo	48.5 lb-ft @ 6,700 rpm
Sistema de combustible	DFI® with Keihin 36mm throttle bodies
Encendido	TCBI with Electronic Advance
Transmisión	6-speed, return shift
Transmisión final	Sealed chain
Asistencia electrónica para el piloto	Economical Riding Indicator, Kawasaki TRaction Control (KTRC - 3 Modes), Anti-lock Brake System (ABS)

## RENDIMIENTO

Suspensión delantera/recorrido del neumático	41mm telescopic fork/4.9 in
Suspensión trasera/recorrido del neumático	Horizontal back-link with adjustable preload, swingarm/5.1 in

Neumático delantero	120/70-17
Neumático trasero	160/60-17
Frenos delanteros	Dual 300mm petal-style discs with two-piston calipers (and ABS)
Frenos traseros	Single 220mm petal-style disc (and ABS)

## DETALLES

Tipo de chasis	Trellis, high tensile steel
Ángulo de dirección/Avance	24.0° / 3.9 in
Largo total	80.9 in
Ancho total	30.1 in
Altura del asiento	41.9 in
Distancia al suelo	5.1 in
Altura del asiento	31.1 in
Dry Weight	381.5 lb** (ABS) / 379.3 lb** (non-ABS) 50-State Model
Peso en orden de marcha	414.5 lb* (ABS) / 412.3 lb* (non-ABS) 50-State Model
Depósito de combustible	4.0 gal
Distancia entre ejes	55.5 in
Características especiales	4.3" All-digital TFT color Instrumentation, Smartphone Connectivity via RIDEOLGY THE APP
Colores disponibles	Metallic Matte Dark Gray/Metallic Spark Black, Metallic Spark Black/Green
Garantía	Garantía limitada de 12 meses

Escanear con cámara para ver videos, características clave y más.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

\*\*Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).  
<sup>1</sup>This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE™ side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2024 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visite [uruguay.kawasaki-la.com](http://uruguay.kawasaki-la.com) para obtener detalles completos del producto.